

Features:

- Miniature relay with high switching capability: 40A.
- Contact form: Form A or Form C.
- Special type of 4000VAC dielectric strength and 6000V surge voltage (1.2/50μS) between coil and contact available.
- IEC60335-1 compliant product is available.

Typical applications:

- Home appliances: air conditioner, heater, etc.
- Vending machine.
- Office equipment: computer, fax machine, etc.
- Electric controlled window, car antenna, door lock, etc.

Approvals

UL, c-UL (File No.): E190598
 CQC (File No.): CQC02001002109, CQC10002050461, CQC21002306488

Contact Data

Contact arrangement	1form C (CO)or 1form A (NO)
Contact resistance	100mΩ Max.(at 1A 6VDC)
Rated voltage	250VAC
Max.switching voltage	277VAC
Rated current	40A
Min. recommended contact load	1A, 6VDC
Breaking capacity max.	11080VA
Contact material	AgSn02
Frequency of operation	360 ops./h
Operate/release time max.	15ms/10ms
Electrical endurance	See electrical endurance graph

Contact ratings

Type	Contact	Load	Cycles
UL 60947-4-1			
SLA-G	A/C(NO)	40A,277VAC,75°C	3×10^4
GB/T 21711.1-2023			
SLA-G	A/C(NO)	40A,277VAC,70°C	2×10^4
Mechanical endurance			$\geq 1 \times 10^7$

Coil Data

Coil voltage range:	5 to 110VDC
Operative range, IEC 61810	2
Coil insulation system according UL	Class F


Coil Data(continued)

Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω (1±10%)	Rated coil powers mW
5	≤3.75	≥0.25	27	900
6	≤4.5	≥0.30	40	900
9	≤6.75	≥0.45	90	900
12	≤9	≥0.60	160	900
15	≤11.25	≥0.75	250	900
18	≤13.5	≥0.90	360	900
24	≤18	≥1.20	640	900
48	≤36	≥2.40	2560	900
110	≤82.5	≥5.50	13400	900



All figures are given for coil without pre-energization, at ambient temperature 20°C

Insulation Data






Initial dielectric strength	
between open contacts	1500VAC
between contact and coil	2500VAC
Clearance/Creepage	
between contact and coil (Clearance)	≥3.5mm(actual)
between contact and coil (Creepage)	≥5mm(actual)
Material group of insulation parts	IIIa
Tracking index of relay	PTI 175V/PTI 250V

Other Data

Material compliance: EU RoHS/ELV, China RoHS, REACH	
Ambient temperature	-40°C to +75°C
Category of environmental protection	
IEC 61810	RTII - flux proof
	RTIII - Sealed type washable
Weight	Approx. 24.0g
Resistance to soldering heat THT (IEC 60068-2-20)	260°C/5s
Packaging/unit	tube, tray



Note:
 (1) Test conditions: room temperature, flux-proof product, resistive load, 1s on, 9s off.
 (2) The above curves are for reference only, and the final result is subject to the experiment.

Dimensions

bottom view
Wiring Diagrams

1c

1a
PCB Layouts (bottom view)

1c

1a

In case of no tolerance shown on outline dimension

If dimension < 1 mm, tolerance: ± 0.2 mm


If dimension 1~5mm, tolerance: ± 0.3 mm

If dimension > 5mm, tolerance: ± 0.4 mm

Notes:

1. The dimension of pin is the size before tinning

2. Tolerance of PCB layout: ± 0.1 mm.

Product Code Structure

- (1) Flux-proof relays can not be used in the environment with pollutants like H₂S, SO₂, NO₂, dust, etc.
- (2) Water cleaning or surface process is not suggested after the flux-proof relays are assembled on PCB.
- (3) Customized special suffix is available after being evaluated by Sanyou.
- (4) C1 suffix stands for product in accordance to IEC60335-1(GWT) & CTI250V.

Examples of Ordering Codes

SLA-S-112DM-G relay SLA, Flux-proof, rated DC voltage 12V, coil power 0.9W, 1NO, and contact material AgSnO₂, 40A.
SLA-S-112DJ-G relay SLA, Flux-proof, rated DC voltage 12V, coil power 0.9W, 1CO, and contact material AgSnO₂, 40A.

Disclaimer

The specification is for reference only. Specifications are subject to change without prior notice.

We could not evaluate all the performance and all the parameters for every possible applications. Thus the users should in a right position to choose suitable product for their own application. For sealed relays, after installation and cleaning, please open the ventilation hole in the case before use. If there is any query, please contact Sanyou for technical services. However it is the user's responsibility to determine which product should be used.