


Features:

- 55A high switching capability
- Most suitable for solar photovoltaic power inverter, UPS
- Contact gap:2.0mm , 2.3mm (IEC62109-2-2011and VDE0126)
- Material compliance (Compliant with RoHS)


Approvals

UL (File No.) : E179745-1-31
 TUV (File No.) : R50540861
 CQC (File No.) : CQC22002336810

Contact Data

| | |
|---------------------------------|---|
| Contact arrangement | 1 Form A |
| Contact material | AgSnO2 |
| Contact Resistance | 100mΩ max(@ 6VDC 20A) |
| Contact Rating (resistive load) | 55A 277VAC |
| Max. Contact Voltage | 277VAC |
| Max. Contact Current | 55A |
| Max. Breaking Capacity | 15235VA |
| Min. recommended contact load | 1A,6VDC |
| Operate Time (at nominal volt.) | ≤20ms |
| Release Time (at nominal volt.) | ≤10ms |
| Electrical endurance | Making 20A, Carrying 55A , Breaking 20A,277VAC,resistive load,85°C ,1s on : 9s off,5×10 ⁴ ops. |

Note:

The above electrical endurance tests are completed with flux-proof product(with vent hole). The venting hole should be opened in electrical endurance test.

Coil Data

| Nominal Voltage VDC | Max. Operate Voltage VDC | Min. Release Voltage VDC | Max. Allowable Voltage VDC | Coil Resistance (1±10%) Ω | Coil Power W | Holding Voltage |
|---------------------|--------------------------|--------------------------|----------------------------|---------------------------|--------------|--|
| 5 | 3.75 | 0.25 | 5.5 | 16 | 1.6 | 50% to 100% Nomi. Volt. (at 23°C) 55% to 100% Nomi. Volt. (at 85°C) |
| 6 | 4.5 | 0.3 | 6.6 | 23 | | |
| 9 | 6.75 | 0.45 | 9.9 | 51 | | |
| 12 | 9 | 0.6 | 13.2 | 90 | | |
| 18 | 13.5 | 0.9 | 19.8 | 203 | | |
| 24 | 18 | 1.2 | 26.4 | 360 | | |

Note:

- (1) Do not apply the maximum voltage on the product continuously for more than 10min to avoid coil heating
- (2) The coil holding voltage is the voltage applied to coil 200ms after the rated voltage
- (3) The contact gap 2.3mm product coil resistance ±15%

Insulation Data

| | |
|-----------------------------|------------------------|
| Insulation resistance | 1000MΩ (500VDC) |
| Initial dielectric strength | |
| between open contacts | 2500VAC, 50/60Hz 1min. |
| between contact and coil | 4500VAC, 50/60Hz 1min. |

Other Data

| | |
|----------------------|--|
| Material compliance | EU RoHS/ELV, China RoHS, REACH |
| Temperature rise | < 70K(After the coil is energized with rated voltage for 200ms,set the holding voltage to 60% of rated voltage,load current carrying 55A, @85°C) |
| Shock resistance | Functional 98m/s ² Destructive 980m/s ² |
| Vibration resistance | 10Hz to 55Hz 1.0mm DA |
| Mechanical endurance | 1×10 ⁵ ops |
| Ambient temperature | -40°C to +85°C |
| Humidity | 5% to 85%RH |
| Weight | Approx. 20g |

| | |
|---------------------------|--------------------|
| Impulse withstand voltage | |
| between contact and coil | AC10,000V 1.2/50μs |




Note:

The above values are initial values


Safety certification load

| Certification | File No. | Approved ratings |
|---------------|----------------|--------------------|
| UL | E179745 | 55A 125/250/277VAC |
| TUV | R50540861 | |
| CQC | CQC22002336810 | |


Dimensions



PCB layout (bottom view)



Wiring Diagrams



Product Code Structure


| | | | | | | | |
|------|----|----|----|---|---|-----|--|
| SMIC | -S | -1 | 12 | Z | M | -XX | |
| | | | | | | | Special parameters: Nil-Standard type, 1-Contact gap 2.3mm |
| | | | | | | | Contact material: Nil-AgSnO ₂ |
| | | | | | | | Contact form:M-Form A |
| | | | | | | | Load current:Z-55A |
| | | | | | | | Coil specification(VDC): 05, 06, 09, 12, 18, 24 |
| | | | | | | | Number of contact groups: 1-1 groups |
| | | | | | | | Protective construction: S- Flux type, SH- Waterproof |
| | | | | | | | Basic model:SMIC |

Note:

- (1) Flux-proof type can not be used in polluted environment containing H₂S, SO₂, NO₂, dust and other pollutants.
- (2) Water cleaning or surface process is not suggested after the flux-proofed relays are assembled on PCB..
- (3) Customer special requirements (XX) shall be evaluated by our company and marked by special suffix.

Coil end parallel circuit (recommended)

Varistor (ZNR) could absorb the coil surge of relay that is recommended.



Disclaimer

This product specification is for reference only, subject to change without prior notice. It is not possible for Sanyou to evaluate all the performance parameter requirements of relays in each specific application field, so customers should choose the suitable product according to the specific application conditions. If you have any questions, please contact us for more technical support, but the customer should be responsible for product selection.